



# European Paint Classe A

## Technical Data Sheet



### Wash resistant, water repelling, interior emulsion paint

A wash resistant, interior emulsion paint with water repelling properties, excellent whiteness with a high coverage and good hide.



#### INTENDED USE

Any normal paintable interior wall surface.



#### SURFACE TREATMENT

Surfaces to treat must be sound, dry, clean, even and free from any loose friable material. For all new walls, in presence of chalking or weak substrates, a priming coat of ADIFIX is recommended.



#### COLOR

Supply colour: White



#### APPLICATION

Brush, roller or spray.



#### THINNING

With water.

Brush, roller: 1st coat 20 - 25%;

2nd coat 15 - 20%.

Spray: 20 - 25%.



#### AVERAGE SPREAD RATE

9 - 10 sq.m./litre per coat



#### DRYING TIME AT 25° C

3 - 4 hours, touch dry.

Recoat time: 6 - 8 hours



#### SPECIFIC GRAVITY

1630 &plusmn; 20 g/



#### VISCOSITY

(Brookfield 20°C): 16000-18000 mPa-s



#### ADVICES

Do not apply with air and surface temperatures below 5°C. or above 28°C. The thinning water should be added gradually, mixing thoroughly and continuously.



#### PAKAGING

drums of lt. 4; lt. 14;



#### DRY SOLID CONTENTS

(%): 68 &plusmn; 1



#### V.O.C. (Directive 2004/42/CE)

28 g/l; Cat. A BA (Max. Value 30 g/l)

Any information supplied whether verbal or in writing, is for guidance only as conditions and feasibility of use may be influenced by external factors beyond our control and is therefore given in good faith but without warranty. Adicolor reserves the right to modify any data and information without notice. Our technical service is available for any further detailed information.

