




Adipac

Technical Data Sheet



Anchoring base coat for wood and walls.


A special high matt, solvent based, filling and anchoring base coat, ideal for the preparation of woodwork and walls to be painted with enamel paints.

 **INTENDED USE**
Preparation of wood, framework, walls and to promote adhesion of the top enamel coat.


 **SURFACE TREATMENT**
Wood and walls must be sanded well then dusted down and clean.

 **COLOR**
Supply colour: White

 **APPLICATION**
Brush, roller or by spray.


 **THINNING**
With mineral turpentine or synthetic thinner Brush, roller: 5-10% - Spray: 10-15%


 **AVERAGE SPREAD RATE**
6 - 8 sq.m./litre per coat

 **DRYING TIME AT 25° C**
1 - 2 hours, dust free
3 - 4 hours, touch dry
Recoat time: after 12 hours


 **SPECIFIC GRAVITY**
1660 \pm 20 g/l

 **VISCOSITY**
(DIN Cup 8, 20°C): 20"

 **ADVICES**
It is important to respect the drying time of the primer or between coats to avoid a removal effect when applying the new coat over the previous one.

 **PAKAGING**
containers lt.0.5x6 units; lt.2.5x2units;

 **DRY SOLID CONTENTS**
(%): 80 \pm 1

 **V.O.C. (Directive 2004/42/CE)**
340 g/l; Cat. G BS (Max. Value 350 g/l)

Any information supplied whether verbal or in writing, is for guidance only as conditions and feasibility of use may be influenced by external factors beyond our control and is therefore given in good faith but without warranty. Adicolor reserves the right to modify any data and information without notice. Our technical service is available for any further detailed information.

