

Exterior Rough Grey Putty

Technical Data Sheet



The specific range in powder form

Cementitious grey skim coat in powder form with excellent spreadability and filling properties. It is ideal for levelling cured cement plasters which present irregularities up to 5 mm of thickness.



INTENDED USE

For interior and exterior cured plasters in general, for structural repairing of the surface, for vertical surfaces, ceilings, Predalles and for floors.



SURFACE TREATMENT

The substrate must be stable, non-chalking, clean from all traces of dust. Powdery plaster must be consolidated with a suitable primer. Moisten the surface before application.



APPLICATION

Mix the contents of each 1 kg pack with 200 ml of water to get a smooth paste free of lumps. Allow to stand for 10'. Apply the paste with a trowel. Wait 2 to 4 h for the application of the second layer. For a finish plaster effect, give a final pass with a sponge trowel. The surface can be painted after 48-72 h.



ADVICES

Do not apply below 5 ° C and above 40 ° C. Do not apply in conditions of strong wind and under full sunshine. Do not use on gypsum plaster.



PAKAGING

1kg, 5kg

Any information supplied whether verbal or in writing, is for guidance only as conditions and feasibility of use may be influenced by external factors beyond our control and is therefore given in good faith but without warranty. Adicolor reserves the right to modify any data and information without notice. Our technical service is available for any further detailed information.

