

Tile Adhesive

Technical Data Sheet

The specific range in powder form

Cementitious powder adhesive with special additives. Easy to work. It has good adhesion properties, hardens without shrinkage and offers considerable resistance.



INTENDED USE

Suitable for indoor and outdoor fixing of tiles on floors and walls; on plaster or mortar walls and screeds provided they are well cured and dry.



SURFACE TREATMENT

The substrate must be flat, solid, well-seasoned and not subject to shrinkage or extreme movements, free from traces of loose particles, dust, grease, etc.. It is advisable to pre-moistening absorbent substrates.



APPLICATION

Mix each kg of the product with 280 ml of water. Mix til smooth and without lumps, let sit a few minutes before applying. Spread the substrate first with the flat side of the trowel and then with the notched trowel. Lay the tiles onto the adhesive layer by applying good pressure. It is advisable to proceed with the application of the adhesive on limited areas. Check occasionally that the contact between adhesive and tile is uniform. The materials applied must be protected from rain for 24 hours after installation. The tiles must be absolutely dry and not very absorbent. Working time will be about 25-35 minutes under normal conditions.



ADVICES

Do not apply below 5 ° C and above 40 ° C. Do not apply in conditions of strong wind and under full sunshine.



PAKAGING

1kg, 5kg

Any information supplied whether verbal or in writing, is for guidance only as conditions and feasibility of use may be influenced by external factors beyond our control and is therefore given in good faith but without warranty. Adicolor reserves the right to modify any data and information without notice. Our technical service is available for any further detailed information.

