

Fondo Universale

Technical Data Sheet

Base coat for Adicolor decorative finishes.

Pigmented, gripping base coat specially formulated for the application of the Sogni Line decorative finishes. This base coat is designed to guarantee the ideal results with maximum durability.



INTENDED USE

Interior or exterior surfaces.



SURFACE TREATMENT

Ensure that the surface is clean, dry and free from peeling paint or any substance that may compromise adhesion. In case of old and powdery walls or in presence of weak paint, apply a coat of ADIFIX primer thinned as specified.



COLOR

Fondo Universale is supplied and can be used WHITE or it can be colored with the use of TINTERS..



APPLICATION

Using a short-pile roller, apply one or two base coats of FONDO UNIVERSALE thinned with 20-30% of water and let dry for minimum 5-6 hours before applying the finish.



THINNING

with 20 to 30% water.



AVERAGE SPREAD RATE

8-10 m²/litre



DRYING TIME AT 25° C

About 30 to 40 min. touch dry; Recoat time: about 6 to 8 hours.



SPECIFIC GRAVITY

1630±20 g/l



VISCOSITY (Brookfield, 20° C)

13000 - 16000 mPa·s



ADVICES

Do not apply with air and surface temperatures below 5°C and above 28°C. All the products must be protected from freezing and well stored under cover. Carefully verify spread rates and the surface area to be coated to avoid running short of product during the working process and reducing the risk of differences in tones. Mix the products well before use. Use fresh clean water for thinning and maintain the same thinning proportions throughout the same job. Wash tools with warm water before the product dries. A correct surface preparation will guarantee a finer finished effect and better product yield. The drying times indicated may vary in relation to the air and surface temperature and the relative humidity. The spread rates of the products have only an indicative value and may vary notably according to the substrate condition and the skill of the applicator.



PAKAGING

Containers lt. 2; lt. 4; lt. 10;



DRY SOLID CONTENTS

70% ± 1 g/l by weight



V.O.C. (Directive 2004/42/CE)

18 g/l; Cat. A BA (Max. Value 30 g/l)

Any information supplied whether verbal or in writing, is for guidance only as conditions and feasibility of use may be influenced by external factors beyond our control and is therefore given in good faith but without warranty. Adicolor reserves the right to modify any data and information without notice. Our technical service is available for any further detailed information.

