

Gran Lavabile & Traspirante

Technical Data Sheet

Emulsion paint for interiors

A washable and air permeable emulsion paint for interiors. Ideal when a cost efficient but accurate work is required. The paint has extra whiteness and a good hide.



INTENDED USE

Any normal paintable interior wall and ceiling surface.



SURFACE TREATMENT

Surfaces to treat must be sound, dry, clean, even and free from any loose friable material. For all new walls, in presence of chalking or weak substrates, a priming coat of ADIFIX is recommended.



COLOR

Supply colour: White



APPLICATION

Brush, roller or spray.



THINNING

With water.

Brush, roller: 1st coat 20 - 25%;
2nd coat 15 - 20%. Spray: 20 - 25%.



AVERAGE SPREAD RATE

9 - 10 sq.m./litre per coat



DRYING TIME AT 25° C

3 - 4 hours, touch dry Recoat time: 6 - 8 hours



SPECIFIC GRAVITY

1690 ± 20 g/l



VISCOSITY

(Brookfield 20°C): 13000-15000 mPa·s



ADVICES

Do not apply with air and surface temperatures below 5°C. or above 28°C. The thinning water should be added gradually, mixing thoroughly and continuously.



PAKAGING

drums of lt. 14;



DRY SOLID CONTENTS

by weight (%): 66 ± 1



V.O.C. (Directive 2004/42/CE)

8 g/l; cat. A BA (Max. Value 30 g/l)

Any information supplied whether verbal or in writing, is for guidance only as conditions and feasibility of use may be influenced by external factors beyond our control and is therefore given in good faith but without warranty. Adicolor reserves the right to modify any data and information without notice. Our technical service is available for any further detailed information.

