

oldFashionClassic



Ver. 1



Technical Data Sheet

Decorative texturing plaster for interiors and exteriors

A unique interior and exterior decorative stone textured plaster that will emphasize a warm and stylish atmosphere. This easy to apply, free-form coating, that can be applied to a thickness of 3-4 mm, is designed to be modeled as pleased, creating attractive textures and effects inspired by nature and your fantasy. The beauty of the finish is enhanced with one or more colored top coats of VELÉ, VELÉ Silver&Gold, SHADÉ or SOGNI SK as pleased.



INTENDED USE

Any well treated, interior or exterior wall surface, either Gypsum plaster based or rendered masonry.



SURFACE TREATMENT

Ensure that the surface is clean and dry. If necessary, apply a coat of ADIFIX primer thinned as specified. According to the finish to be applied, you may require a basecoat of FONDO UNIVERSALE either white or tinted and thinned with 10 to 15% water.



APPLICATION

Consult our "Show Effects" catalogue and the application DVD to see the many finishes you can create or you can also easily invent new personalized effects as pleased.



THINNING

Ready to use



AVERAGE SPREAD RATE

Highly variable according to the chosen effect.



DRYING TIME AT 25° C

About 6 to 8 hours
Recoat time: about 10 to 12 hours



SPECIFIC GRAVITY

1680 ± 20 g/l



VISCOSITY

(Brookfield 20°C): 50.000 to 70.000 mPa.s



V.O.C. (Directive 2004/42/CE)

Cat. L BA - Direttive 2004/42/CE - Val Max.: 200 g/l - Val Eff.: 29 g/l

Any information supplied whether verbal or in writing, is for guidance only as conditions and feasibility of use may be influenced by external factors beyond our control and is therefore given in good faith but without warranty. Adicolor reserves the right to modify any data and information without notice. Our technical service is available for any further detailed information.

