

Paviflex ECO

Technical Data Sheet



Waterborne floor paint for interiors and exteriors

PAVIFLEX ECO is a modern, waterborne, low odor, rapid drying, satin paint for floors, ideal for both interiors and exteriors. It is an easy to use one-pack product formulated with top quality special modified acrylic resins that give the product outstanding characteristics of durability, hard wearing, high adhesion even to difficult surfaces such as ceramics and can it also resist to light tire traffic. The product is also recommended for use on walls when exceptional resistances are required.



INTENDED USE

Finish coat for floors in staircases, garages, terraces and balconies.



SURFACE TREATMENT

Surfaces to treat must be sound, perfectly dry, clean and even. Degrease and brush down and clean the surface well.



COLOR

Grey RAL 7038, Red RAL 3009



APPLICATION

By brush or roller.

Cement: apply the first coat thinned with 10% water and the 2nd coat undiluted.

Ceramics: glossy surfaces should be dulled by sanding, clean and apply 2 coats undiluted.

Wood: apply 2 coats of undiluted Paviflex Eco.



THINNING

Ready to use or if necessary with max. 10% water.



AVERAGE SPREAD RATE

6 - 8 sq.m./litre per coat



DRYING TIME AT 25° C

About 45 minutes; to foot traffic abt. 90 minutes. Recoating after 4 hours



SPECIFIC GRAVITY

1270 ± 20 g/l



VISCOSITY

(Brookfield 30° C): 1400-1600 mPa·s



ADVICES

Check that the substrate does not present any problems of humidity. Do not apply with air or surface temperature below 5°C and above 28°C. It is advisable to always use same batch number in case you are using more packs for the same job. Clean working tools with warm water.



PAKAGING

containers lt.0.75x6 units; lt.2.5x2 units



DRY SOLID CONTENTS

(%): 51 ± 1



V.O.C. (Directive 2004/42/CE)

20 g/l; Cat. I BA (Max. Value 140 g/l)

Any information supplied whether verbal or in writing, is for guidance only as conditions and feasibility of use may be influenced by external factors beyond our control and is therefore given in good faith but without warranty. Adicolor reserves the right to modify any data and information without notice. Our technical service is available for any further detailed information.

