

Interir putty

Technical Data Sheet



Interir putty

An ultra white putty for interior use, really easy to apply, to smooth and to sand. It has good durability and hardness when dry. Excellent adhesion and resistance to shrinking. Recommended to fill holes and cracks up to 2-3 mm in a single application. Studied for concrete, cement, plasterboard, wall masonry, stone, brick, gypsum, old paints and wood.



INTENDED USE

Any interior masonry or wood surface.



SURFACE TREATMENT

Surfaces to treat must be sound, dry, clean and free from any loose friable material. For all new walls or in presence of chalking or weak substrates, apply a priming coat of ADIFIX.



APPLICATION

Apply with flex spatula. Max thickness: 3 mm per coat.



THINNING

Ready to use



AVERAGE SPREAD RATE

Variable, according to thickness applied.



DRYING TIME AT 25° C

sandable after 2 hours. Recoat time: 6-8 hours.



ADVICES

Do not apply with air and surface temperatures below 5°C or above 28°C.



PAKAGING

250g, 500g, 1kg, 5kg, 20kg.

Any information supplied whether verbal or in writing, is for guidance only as conditions and feasibility of use may be influenced by external factors beyond our control and is therefore given in good faith but without warranty. Adicolor reserves the right to modify any data and information without notice. Our technical service is available for any further detailed information.

