



Traspirante Professionale

Technical Data Sheet



Interior wall paint

Professional quality, water based interior paint. Good hide, breathability and extra whiteness.



INTENDED USE

Any normal paintable interior wall and ceiling surface.



SURFACE TREATMENT

Surfaces to treat must be sound, dry, clean, even and free from any loose friable material. For all new walls, in presence of chalking or weak substrates, a priming coat of ADIFIX is recommended.



COLOR

Supply colour: White



APPLICATION

Brush, roller or spray.



THINNING

With water.

Brush, roller: 1st coat 30 - 40%;
2nd coat 25 - 30%. Spray: 35 - 40%.



AVERAGE SPREAD RATE

8 - 10 sq.m./litre per coat



DRYING TIME AT 25° C

3 - 4 hours, touch dry

Recoat time: 6 - 8 hours



SPECIFIC GRAVITY

1680 ± 20 g/l



VISCOSITY

(Brookfield 20° C): 17000- 19000 mPa·s



ADVICES

Do not apply with air and surface temperatures below 5°C. or above 28°C. The thinning water should be added gradually, mixing thoroughly and continuously, especially in case of coloured product.



PAKAGING

containers lt. 4; lt. 14;



DRY SOLID CONTENTS

(%): 70 ± 1



V.O.C. (Directive 2004/42/CE)

21 g/l; Cat. A BA (Max. Value 30 g/l)

Any information supplied whether verbal or in writing, is for guidance only as conditions and feasibility of use may be influenced by external factors beyond our control and is therefore given in good faith but without warranty. Adicolor reserves the right to modify any data and information without notice. Our technical service is available for any further detailed information.

