

UNIVERSAL COLORANTS

for the **ISTANT COLOUR** professional tinting system

Universal colorants for the Adicolor, **ISTANT COLOUR** professional tinting system. Ideal for producing even difficult tones also for exteriors

SISTEMA
**ISTANT
 COLOUR**
 TINTOMETRICO
 PROFESSIONAL



V.O.C. = 0 (zero)

Intended use:

For use with colorant dispenser in the coloring of both waterborne and solvent based paints.

	Colorant Code	COLOUR and Colour Index	Characteristics	PIGMENT %	DENSITY kg/l
1	XA	WHITE - PW 6	for Interior / Exterior use	(54)	1,74
2	XB	YELLOW OXIDE - PY 42	for Interior / Exterior use	(52)	1,64
3	XZ	ORANGE OXIDE - PR101	for Interior / Exterior use	(25)	1,35
4	XD	RED OXIDE - PR 101	for Interior / Exterior use	(52)	1,72
5	XE	RED - PR 112	moderate resistance to light - full tone	(14)	1,28
6	XF	ORANGE - PO 5	for Interior / Exterior use	(19)	1,34
7	XL	VIOLET - PV 23	for Interior / Exterior use	(5)	1,17
8	XH	GREEN - PG 7	for Interior / Exterior use	(18)	1,28
9	XJ	BLACK (dil) - PB 7	for Interior / Exterior use	(8)	1,38
10	XK	BLUE - PB 15:2	for Interior / Exterior use	(20)	1,16
11	XP	BLACK - PB 7	for Interior / Exterior use	(20)	1,12
12	XR	YELLOW Bismuth-van - PY 184	high performance - Exterior use	(55)	2,01
13	XS	YELLOW - PY 74	moderate resistance to light - full tone	(35)	1,34
14	XY	MAGENTA - PR 122	for Interior / Exterior use	(7)	1,25
15	XU	RED - PR 168	high performance - Exterior use	(15)	1,42
16	XV	GREEN Chromium ox. - PG 17	for Interior / Exterior use	(55)	1,97

Packaging size: Supplied in 1 litre containers in packs of 3 x 1lt.

Advices:

Mix the colorante thoroughly before emptying into the dispenser canister. It is advisable to empty the entire pack into the canister once opened.

The colorants need to be kept constantly well mixed in the dispenser canisters.

Clean tools with warm water. Store the product well protected from freezing and excess heat.