

## TECHNICAL DATA SHEET

# SANDÉ

Decorative sandy effect finish



### PRODUCT DESCRIPTION

Waterborne decorative effect finish based on natural quartz sand, acrylic resins in aqueous emulsion and additives which give the product its excellent film-forming properties and high workability. **SANDÉ** is ideal for both classic and modern environments with its absolute matt appearance, a pleasant sandy pattern and a fine-textured materic touch.

### INTENDED USE

<b>Destination:</b>	<b>Specific for:</b>
Interiors	Cement based surfaces, gypsum and plasterboard
	Walls

### SURFACE PREPARATION

The correct surface preparation of the substrate will guarantee the best results in terms of product yield, appearance and resistance in time of the finish

#### CEMENT, GYPSUM AND PLASTERBOARD SURFACES

- **New unpainted surfaces** Clean the surface and remove all possible traces of dust or dirt. Treat the substrate with a priming coat of **ADIFIX** thinned as specified and allow to dry. Proceed with the application of a basecoat using **FONDO UNIVERSALE** thinned in the recommended doses and colored in a tone similar to that of the finish.
- **Previously painted surfaces:** Check that the state of the existing paintwork is in excellent condition, if so, proceed directly with the application of the **FONDO UNIVERSALE**, as described in the previous paragraph. If the surface shows signs of defects, such as peeling or chalking, remove any loose parts that would compromise the correct adhesion of the product then proceed as indicated hereabove for **New unpainted surfaces**.

#### Additional information:

- The substrates must in every case be sound, dry and clean.
- Remove all possible traces of dust, dirt or other impurities before the application.
- The nature of the support can change the final appearance of product.

## INSTRUCTIONS FOR USE









### Tools used for application

- Sandé brush

### APPLICATION METHOD

- Once the colored basecoat is well dry, proceed with the application of **SANDÉ** applying one coat of product with the specific **Sandé brush** using uneven crossed brush strokes, always maintaining abundance of product on the brush.
- Start the applications from the top corner of the wall and work downwards. Take care to ensure a regular and pleasant distribution of the sand on the surface, avoiding any undesired clustering of the sand.

## TECHNICAL SPECIFICATIONS

	Indicative spread rate per coat (m <sup>2</sup> /ℓ)	-	-	6 to 8
	Thinning (%)	-	water	Ready to use or with max. 5%
	Touch dry (at 25°C)	-	hours	4 to 6
	Totally dry	-	hours	24
	Recoat time (if necessary)	-	hours	10 to 12
	Density (kg/ℓ, ±0.02)	ISO 2811	at 20°C	1.600
	Viscosity Brookfield (mPa·s)	ISO 2555	at 20°C	14,000 to 16,000
<b>pH</b>	pH value (±0.5)	-	-	8.5
	Solid contents by weight (% , ±1)	-	-	67

\* the data herein reported refer to measurements made at the end of the production process.

## TOOL CLEANING

- Clean working tools immediately after use with soap and water.

## WARNINGS AND ADDITIONAL INFORMATION

- Do not apply with air and surface temperatures below 5°C and above 28°C.
- The drying times indicated may vary in relation to the relative humidity and the existing temperature.
- Carefully verify spread rates and the surface area to be coated to avoid running short of product during the working process. This will also reduce the risk of eventual differences in tones.
- The spread rates and yields of the product are given as guidance only and may vary notably according to the substrate condition and the application method used.
- Stir the product thoroughly before use.
- Remove masking tapes before total drying of the product.
- It is recommended to always carry out a sample test on the specific surface before starting the final work.

## HANDLING AND STORAGE

- Consult the relative **Safety Data Sheet** for the detailed health and safety information.
- Use the product in accordance with your current health and safety legislation regulations in force.
- Do not disperse the packaging in the environment
- Store the undiluted product, in original well sealed containers, in a cool and dry area, sheltered from frost and sources of heat.
- Protect the product at all times from freezing.

## COLORS

### Colors available:

- White

### Product included in the Adicolor tinting system:

<b>Reference color-guides</b>	<ul style="list-style-type: none"><li>▪ The specific product catalogue/color-guide</li><li>▪ Decora©tive book</li></ul>
-------------------------------	---

- If the product requires coloring, be sure to use product bases and colorants belonging to the same batch number for the same job to avoid slight variations in color from showing.
- When using multiple cans for the same job, we recommend to mix the relative products together before use. We also recommend to use products from the same batch numbers for the same application area.
- The colors presented in our catalogues are for guidance only, even when true product applications are shown. Colors may vary notably in relation to the application, the substrate, light reflectance and the environment.
- It is recommended to test and validate colors before carrying out the final job in order to avoid any disputes.