

## TECHNICAL DATA SHEET

# Linea ADISTUC STUCCO IN PASTA

Filler and putty in paste form



### PRODUCT DESCRIPTION

Ready to use, ultra-white filler and putty, easy to apply and to sand. Excellent adhesion. Ideal both for filling holes and cracks up to 2-3 mm and for smoothing wall surfaces.

### INTENDED USE

Destination:	Specific for:
Interiors	Cement based surfaces, gypsum and plasterboard, Stone, Wood

### SURFACE PREPARATION

The correct surface preparation of the substrate will guarantee the best results in terms of product yield, appearance and resistance in time of the finish

#### CEMENT, GYPSUM AND PLASTERBOARD SURFACES

- **New unpainted surfaces:** Clean the surface and remove all possible traces of dust or dirt. If necessary, treat the substrate with a priming coat of **ADIFIX** thinned as specified
- **Previously painted surfaces:** Check that the state of the existing paintwork is in excellent condition, if so, proceed directly with the application of the putty. If the surface shows signs of defects, such as peeling or chalking, remove any loose parts that would compromise the correct adhesion of the product and treat the substrate with a priming coat of **ADIFIX** thinned as specified

#### WOOD

- **New wood:** Clean the surface and remove all possible traces of dust or dirt.
- **Previously painted wood:** Check that the state of the existing paintwork is in excellent condition, if so, proceed directly with the application of the filler. If the surface shows signs of defects, such as peeling or chalking, remove any loose parts that would compromise the correct adhesion of the product

The information reported herein is the result of our best experience and technical knowledge to date and is given in good faith and for guidance only. ADICOLOR cannot be held responsible for the actual use of the product since the application is influenced by many factors and is carried out beyond our control. The data and information herein may be subject to changes, even without notice, as a result of any technical development.  
This technical data sheet cancels and replaces any existing previous version.

### Additional information:

- The substrates must in every case be sound, dry and clean.
- Remove all possible traces of dust, dirt or other impurities before the application.
- The nature of the support can change the final appearance of product.

## INSTRUCTIONS FOR USE








### Tools used for application

- Flexible trowel

## APPLICATION METHOD

- Apply **ADISTUC** up to a maximum thickness of 2 to 3 mm per coat.
- Before proceeding with the finishing paint, sand and apply a coat of primer **ADIFIX** thinned as recommended.

## TECHNICAL SPECIFICATIONS

	Indicative spread rate per coat (kg/m <sup>2</sup> )	-	-	1,5 per mm of thickness
	Thinning (%)	-	water	Ready to use
	Touch dry (at 25°C)	-	hours	2 to 4 (variable according to thickness)
	Totally dry	-	hours	6 to 8
	Recoat time	-	hours	Sandable after: 2 Recoatable after: 6 to 8
	Density (±0.02)	ISO 2811	at 20°C	1.800
pH	pH value (±0,5)	-	-	7.5
	Solid contents by weight (% , ±1)	-	-	75

\* the data herein reported refer to measurements made at the end of the production process.

## TOOL CLEANING

- Clean working tools immediately after use with soap and water.

## WARNINGS AND ADDITIONAL INFORMATION

- Do not apply with air and surface temperatures below 5°C and above 28°C.
- The drying times indicated may vary in relation to the relative humidity and the existing temperature.
- Carefully verify spread rates and the surface area to be coated to avoid running short of product during the working process. This will also reduce the risk of eventual differences in tones.
- The spread rates and yields of the product are given as guidance only and may vary notably according to the substrate condition and the application method used.
- Stir the product thoroughly before use.
- Remove masking tapes before total drying of the product.
- It is recommended to always carry out a sample test on the specific surface before starting the final work.

## HANDLING AND STORAGE

- Consult the relative **Safety Data Sheet** for the detailed user's health and safety information.
- Use the product in accordance with your current health and safety legislation regulations in force.
- Do not disperse the packaging in the environment
- Store the undiluted product, in original well sealed containers, in a cool and dry area, sheltered from frost and sources of heat.
- Protect the product at all times from freezing.

## COLORS

### Colors available:

- White