

## TECHNICAL DATA SHEET

# ADISTUC range STUCCO IN POLVERE

Putty and filler in powder form



### PRODUCT DESCRIPTION

Putty and filler in powder form, based on Gypsum, carbonates and cellulose resins. Ideally suited for smoothing and leveling interior walls and for the adhesion of Gypsum plaster ornaments. It dries rapidly and is easy to sand.

### INTENDED USE

#### Destination:

Interiors

#### Specific for:

Cement based surfaces,  
gypsum and plasterboard,  
Walls

### SURFACE PREPARATION

The correct surface preparation of the substrate will guarantee the best results in terms of product yield, appearance and resistance in time of the finish

#### CEMENT, GYPSUM AND PLASTERBOARD SURFACES

- **New unpainted surfaces:** Clean the surface and remove all possible traces of dust or dirt. Apply **STUCCO IN POLVERE**. Before proceeding with the finishing paint, apply a priming coat of **ADIFIX** thinned as specified
- **Previously painted surfaces:** Check that the state of the existing paintwork is in excellent condition, if so, proceed directly with the application of the putty. If the surface shows signs of defects, such as peeling or chalking, remove any loose parts that would compromise the correct adhesion of the product then proceed as indicated hereabove for **New unpainted surfaces**.

#### Additional information:

- The substrates must in every case be sound, dry and clean.
- Remove all possible traces of dust, dirt or other impurities before the application.
- The nature of the support can change the final appearance of product.

## INSTRUCTIONS FOR USE





### Tools used for application

- Flexible stainless-steel trowel

### APPLICATION METHOD

- Apply the product after a correct preparation of the paste, mixing the powder with water.

## TECHNICAL SPECIFICATIONS

	Thinning (%)	-	water	50 to 60 % water (for the preparation of the mixture)
	Touch dry (at 25°C)	-	hours	2 to 4 (variable according to thickness)
	Totally dry	-	hours	6 to 8
	Recoat time	-	hours	Sandable after: 2 Recoatable after: 6 to 8
	Pot life	-	minutes	60 to 90

## TOOL CLEANING

- Clean working tools immediately after use with soap and water.

## WARNINGS AND ADDITIONAL INFORMATION

- Do not apply with air and surface temperatures below 5°C and above 28°C.
- The drying times indicated may vary in relation to the relative humidity and the existing temperature.
- Carefully verify spread rates and the surface area to be coated to avoid running short of product during the working process.
- Stir the product thoroughly before use.
- It is recommended to always carry out a sample test on the specific surface before starting the final work.

## HANDLING AND STORAGE

- Consult the relative **Safety Data Sheet** for the detailed user's health and safety information.
- Use the product in accordance with your current health and safety legislation regulations in force.
- Do not disperse the packaging in the environment
- Store the undiluted product, in original well sealed containers, in a cool and dry area, sheltered from frost and sources of heat.

## COLORS

### Colors available:

- White