

TECHNICAL DATA SHEET

EASYWAX

Waterborne wax



PRODUCT DESCRIPTION

Waterborne bleached wax for giving protection and extra shine to polished plasters decorative finishes. The product is water-repellent and non-yellowing.

INTENDED USE

Destination:	Specific for:
Interiors	For the protection of polished plaster finishes
	Walls

SURFACE PREPARATION

The correct surface preparation of the substrate will guarantee the best results in terms of product yield, appearance and resistance in time of the finish

Additional information:

- The substrates must in every case be sound, dry and clean.
- Remove all possible traces of dust, dirt or other impurities before the application.
- The nature of the support can change the final appearance of product.

INSTRUCTIONS FOR USE






Tools used for application

- Sponge or lint-free cloth
- Woolen cloth

APPLICATION METHOD

- Before applying EASYWAX, ensure that the polished plaster is completely dry (24 to 48 hours minimum after application, depending on the thickness).
- Mix the wax thoroughly. If it results to be too hard to use, dilute it with a little hot water or keep it in a warm place till it becomes more fluid.
- Ensure that the surface to coat is perfectly dry and clean then apply EASYWAX with a sponge or synthetic lint-free cloth.
- When the wax starts to dry, polish the surface well using a clean wool or cotton cloth.
- In case of necessity, to remove **EASYWAX** it is sufficient to sand down with abrasive paper until the surface becomes opaque.

TECHNICAL SPECIFICATIONS

	Indicative spread rate per coat (m ² /ℓ)	-	-	15 to 20
	Thinning (%)	-	-	Ready to use
	Density (kg/ℓ, ±0.02)	ISO 2811	at 20°C	0.900
	Viscosity Brookfield (mPa·s)	ISO 2555	at 20°C	3,500 to 4,500
pH	pH value (±0.5)	-	-	8.5
	Solid contents by weight (% , ±1)	-	-	15

* the data herein reported refer to measurements made at the end of the production process.

TOOL CLEANING

- Clean working tools immediately after use with soap and water.

WARNINGS AND ADDITIONAL INFORMATION

- Do not apply with air and surface temperatures below 5°C and above 28°C.
- The drying times indicated may vary in relation to the relative humidity and the existing temperature.
- Carefully verify spread rates and the surface area to be coated to avoid running short of product during the working process. This will also reduce the risk of eventual differences in effect.
- The spread rates and yields of the product are given as guidance only and may vary notably according to the substrate condition and the application method used.
- Stir the product thoroughly before use.
- Remove masking tapes before total drying of the product.
- It is recommended to always carry out a sample test on the specific surface before starting the final work.

HANDLING AND STORAGE

- Consult the relative **Safety Data Sheet** for the detailed user's health and safety information.
- Use the product in accordance with your current health and safety legislation regulations in force.
- Do not disperse the packaging in the environment
- Store the undiluted product, in original well sealed containers, in a cool and dry area, sheltered from frost and sources of heat.
- Protect the product at all times from freezing.

COLORS

Colors available:

- Transparent

EASYWAX is not to be colored