

TECHNICAL DATA SHEET

ADESIVO PER FOIL

Adhesive specific for foil



PRODUCT DESCRIPTION

Waterborne glue specifically studied for the application of foil in decorative wall coatings.

INTENDED USE

Destination:

Interiors

Specific for:

Wall surfaces

SURFACE PREPARATION

The correct surface preparation of the substrate will guarantee the best results in terms of product yield, appearance and resistance in time of the finish

- The substrates must in every case be sound, dry and clean.
- Remove all possible traces of dust, dirt or other impurities before the application.

INSTRUCTIONS FOR USE

Tools used for application

- Brush
- Roller
- Sponge

APPLICATION METHOD

- After having cut the foil to the desired size, spread the glue on the chosen support covering the area where you want the foil to go. Wait 5 minutes and apply a second coat of product. Press the foil firmly with a sponge or a clean roller to facilitate adhesion. Wait 2 or 3 hours then gently tear away the excess parts of the foil.

The information reported herein is the result of our best experience and technical knowledge to date and is given in good faith and for guidance only. ADICOLOR cannot be held responsible for the actual use of the product since the application is influenced by many factors and is carried out beyond our control. The data and information herein may be subject to changes, even without notice, as a result of any technical development.
This technical data sheet cancels and replaces any existing previous version.

TECHNICAL SPECIFICATIONS

🔹	Thinning (%)	-	-	Ready to use
🗑️	Density (kg/ℓ, ±0.02)	ISO 2811	at 20°C	1.030
●	Viscosity Brookfield (mPa·s)	ISO 2555	at 20°C	2,000 to 4,000

* the data herein reported refer to measurements made at the end of the production process.

TOOL CLEANING

- Clean working tools immediately after use with soap and water.

WARNINGS AND ADDITIONAL INFORMATION

- Do not apply with air and surface temperatures below 12°C and above 30°C.
- Carefully verify spread rates and the surface area to be coated to avoid running short of product during the working process.
- It is recommended to always carry out a sample test on the specific surface before starting the final work.

HANDLING AND STORAGE

- Consult the relative **Safety Data Sheet** for the detailed user's health and safety information.
- Use the product in accordance with your current health and safety legislation regulations in force.
- Do not disperse the packaging in the environment
- Store the undiluted product, in original well sealed containers, in a cool and dry area, sheltered from frost and sources of heat.
- Protect the product at all times from freezing.